


## Batterie al piombo VRLA

### VRLA - Valve regulated Lead Acid batteries

12 V 3,4 Ah




BP12-3,4

Bulk **20**

Tensione nominale : 12 V  
Tensione carica tampone 13,8 V / Ciclico 14,5 V a 20 °C  
Capacità: 3,4 Ah

Terminali Faston 4,8 mm

12 V 4,5 Ah




BP12-4,5

Bulk **20**

Tensione nominale : 12 V  
Tensione carica tampone 13,8 V / Ciclico 14,5 V a 20 °C  
Capacità: 4,5 Ah

Terminali Faston 4,8 mm

12 V 7,0/7,2/7,5 Ah



7,0 Ah

BP12-7,0 Bulk **20**



7,2 Ah

BP12-7,2 Bulk **20**




7,5 Ah

BP12-7,5 Bulk **20**

Tensione nominale : 12 V  
Tensione carica tampone 13,8 V / Ciclico 14,5 V a 20 °C  
Capacità: 7,0/7,2/7,5 Ah

Terminali Faston 4,8 mm

12 V 12 Ah



BP12-12

Bulk **20**

Tensione nominale : 12 V  
Tensione carica tampone 13,8 V / Ciclico 14,5 V a 20 °C  
Capacità: 12 Ah

Terminali Faston 6,3 mm

